

Wire Reinforced Standard Range Exhaust Hose



Wire Reinforced Standard Range Exhaust Hose					
Temperature rating - Continuous: 100°C, intermittent: Contact Halyard					
Part No.	Reference	I.D.		Bend Radius	Max. Length
		inch	mm		
H000518	HS32	1.25	32	130	60
H000519	HS38	1.50	38	150	60
H000520	HS40	1.58	40	160	60
H000521	HS44	1.77	45	170	60
H000522	HS51	2.01	51	180	60
H000523	HS60	2.36	60	190	60
H000524	HS63	2.50	63.5	200	60
H000525	HS76	3.00	76	250	60
H013763	HS90	3.55	90	330	60
H013764	HS102	4.00	102	410	60
H018617	HS127	5.00	127	560	60
H019437	HS152	6.00	152	680	60
H019438	HS203	8.00	203	995	60
Not available with soft cuffed ends					



Wire Reinforced 'HalFlex' Ultra Flexible Exhaust Hose



Wire Reinforced 'HalFlex' Ultra Flexible Exhaust Hose					
Temperature rating - Continuous: 100°C, intermittent: Contact Halyard					
Part No.	Reference	I.D.		Bend Radius	Max. Length
		inch	mm		
H022112	HFX38	1.50	38	75	11
H022113	HFX41	1.61	41	85	6
H022114	HFX44	1.73	44	90	12
H022115	HFX51	2.00	51	105	12
H022116	HFX60	2.36	60	120	12
H022117	HFX63	2.50	63	125	6
H022118	HFX76	3.00	76	175	12
H022119	HFX89	3.50	89	205	12
H022120	HFX102	4.00	102	235	12
H022121	HFX113	4.50	113	260	11
H022122	HFX127	5.00	127	295	12
H022123	HFX152	6.00	152	350	12
H022124	HFX177	7.00	177	410	6
H022125	HFX203	8.00	203	470	6
H022126	HFX254	10.00	254	700	6
H022127	HFX305	12.00	305	840	6
H022128	HFX356	14.00	356	N/A	4.5
H022129	HFX406	16.00	406	N/A	3.5
H022130	HFX458	18.00	458	N/A	2
Available as wired to end or with soft cuffed ends to aid hose clamping					

